

Product datasheet

Specifications



APC Easy UPS On-Line SRV Battery Pack (6/10kVA) for Extended Runtime Model 240V, 2160VAh, rackmount with kit, 3U

SRV240RLBP-9A

Overview

Lead time Usually in Stock

Main

Number of rack unit 3U

Battery type Lead-acid battery

Provided equipment User manual
Battery cable
Rack mounting brackets

Batteries & Runtime

Number of battery blocks per string 20

Device mounting Rack mount

Number of battery filled slots 0

Number of battery free slots 0

Battery voltage 240 V

Physical

Colour Black

Height 13.3 cm

Width 43.8 cm

Depth 60.6 cm

Net weight 63 kg

Mounting mode Rack-mounted with kit

USB compatible No

Conformance

Product certifications CE
UKCA
EAC
EN/IEC 62040-1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental

| | |
|---------------------------------------|-------------------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % non-condensing |
| Operating altitude | 0...3000 m |
| Ambient air temperature for storage | -15...40 °C |
| Storage Relative Humidity | 0...95 % non-condensing |
| Storage altitude | 0...15000 m |

Packing Units

| | |
|------------------------------|-------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 25 cm |
| Package 1 Width | 87 cm |
| Package 1 Length | 58 cm |
| Package 1 Weight | 70 kg |

Offer Sustainability

| | |
|----------------------------|--|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration |
| RoHS exemption information | Yes |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|

Recommended replacement(s)